

## **Product Information**

## 16 90 130 SB

Universal Stripping Tool for building and industrial cables



MM

| • | With          | opening | spring | and | locking | device |
|---|---------------|---------|--------|-----|---------|--------|
| - | <b>VVILII</b> | opening | spring | unu | locking | ucvicc |

- For stripping all common round and damp-proof installation cables between  $\emptyset$  8.0 13.0 mm (e.g. 3 x 1.5 mm<sup>2</sup> up to 5 x 2.5 mm<sup>2</sup>)
- Also for use in conduit and distribution boxes
- Body: glass fibre reinforced plastic
- For use in confined and difficult to access work areas
- Especially suitable for larger cross-sections and for difficult insulating materials
- No adjustment of blades to cutting depth required
- Stripping device for conductors and strands  $1.5\ mm^2$  and  $2.5\ mm^2$
- Two-way length stop (ideal for right and left-handers)
- Fastening device on the end of the handle (drop protection system)

| General                                    |  |  |  |  |
|--|--|--|--|--|
| Article No.                                | 16 90 130 SB   |  |  |  |
| EAN  | 4003773076940  |  |  |  |
| Weight                                     | 47 g   |  |  |  |
| Dimensions                                 | 130 x 88 x 32 mm   |  |  |  |
| REACH compliant                            | does not contain SVHC  |  |  |  |
| RoHS compliant                             | not applicable   |  |  |  |
| Technical details                          |  |  |  |  |
| Stripping capacities in square millimetres | 1.5 / 2.5 mm²  |  |  |  |
| Cable type                                 | round cable, e.g.: 3 x 1,5 mm <sup>2</sup> up to 5 x 2,5 mm <sup>2</sup> |  |  |  |

Technical changes and errors excepted

## **KNIPEX** Quality – Made in Germany









