

## Product Information

# 74 06 250 T

## High Leverage Diagonal Cutter

- For very tough, continuous use
- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges additionally induction-hardened (cutting edge hardness approx. 64 HRC), for all sorts of wire including piano wire
- Pliers with integrated, insulated tether attachment point for a tool tether



⚡ 1000V 



| General  |  |
|--|--|
| Article No.                                    | 74 06 250 T  |
| EAN  | 4003773081500  |
| pliers   | chrome-plated  |
| head   | chrome-plated  |
| handles  | insulated with multi-component grips, VDE-tested with integrated insulated tether attachment point |
| Weight   | 465 g  |
| Dimensions                                     | 250 x 61 x 29 mm   |
| Standard                                       | DIN ISO 5749 DIN EN 60900 IEC 60900  |
| REACH compliant                                | does not contain SVHC  |
| RoHS compliant                                 | not applicable   |
| Technical details                              |  |
| Cutting capacities medium hard wire (diameter) | Ø 4.6 mm   |
| Cutting capacities hard wire (diameter)        | Ø 3.5 mm   |
| Cutting capacities piano wire (diameter)       | Ø 3.0 mm   |
| Drop Protection System                         | yes  |
| VDE tested                                     | yes  |

Technical changes and errors excepted

