

## Product Information

# 95 05 20 SB

## Angled Electricians' Shears



MM  $\angle 45^\circ$

- Precision-ground blades with fine serrations for a clean, non-slip cut
- Adapted to the hand: angled blades and optimised handle design for improved ergonomics
- Two crimping areas for wire ferrules of 0.5 - 6 mm<sup>2</sup> and 10 - 25 mm<sup>2</sup>
- Suitable for cutting of the following cables: 1 x 25 mm<sup>2</sup> such as H01 N2-D flexible / stranded rubber connecting and control cables for arc welding, 5 x 2.5 mm<sup>2</sup> such as H07 RN-F flexible and stranded heavy rubber hose line cable, flexible and stranded cables up to Ø 15 mm, 5 x 1.5 mm<sup>2</sup> such as damp-proof installation cables
- Includes opening spring and lock for easy storage
- Tether attachment point can be used with KNIPEX Tethered Tools System
- Cutting edges made from stainless steel, hardness of cutting edges 56 HRC
- Not suitable for cutting solid conductors
- Practical belt pouch (00 19 75 LE) available separately

| General         |  |
|-----------------|--|
| Article No.     | 95 05 20 SB  |
| EAN             | 4003773082699  |
| Shears          | mirror polished  |
| handles         | with multi-component grips, glass fibre reinforced plastic |
| Weight          | 190 g  |
| Dimensions      | 160 x 76 x 21 mm   |
| REACH compliant | does not contain SVHC                                      |
| RoHS compliant  | not applicable   |

*Technical changes and errors excepted*











